



PRODUCT-DETAILS

# MS165-80

## MS165-80 Manual Motor Starter 70 ... 80 A



| General Information    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type  | MS165-80                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Product ID             | 1SAM451000R1019                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| EAN                    | 4013614536632                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Catalog Description    | MS165-80 Manual Motor Starter 70 ... 80 A                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Long Description       | <p>MS165 is a compact and powerful range for motor protection up to 45 kW (400 V) / 80 A in width of 55 mm. They offer a reliable protection for motors in the event of overload or phase failure. The devices have trip class 10.</p> <p>This type has also a clear and reliable indication of fault in a separate window in the event of short-circuit tripping. Further features are the build-in disconnect function, temperature compensation, trip-free mechanism and a rotary handle with a clear switch position indication. The manual motor starter (also known as motor protection circuit breaker or manual motor protector) is suitable for three- and single phase applications. The handle is lockable to protect against unauthorized changes. Auxiliary contacts, signaling contacts, undervoltage releases, shunt trips, power in-feed blocks are available as accessory. These are suitable throughout the MS116/MS132/MS165 range.</p> |
| Ordering               |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Minimum Order Quantity | 1 piece                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |

Customs Tariff Number

85362090

| Popular Downloads                 |                 |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 2CDC131083D0201 |
| Instructions and Manuals          | 2CDC131081M6801 |
| Instructions and Manuals (Part 2) | 2CDC131060M0202 |
| Ex Operating Instructions         | 2CDC131087M6801 |
| Time-Current Characteristic Curve | 1SAM400505F0009 |
| I <sup>2</sup> t Characteristic   | 1SAM400506F0001 |
| Cut-off Current Characteristic    | 1SAM400507F0001 |
| CAD Dimensional Drawing           | 2CDC001079B0201 |
| Dimension Diagram                 | 1SAM400401F0001 |

| Dimensions                 |           |
|----------------------------|-----------|
| Product Net Width          | 55 mm     |
| Product Net Height         | 142.65 mm |
| Product Net Depth / Length | 122 mm    |
| Product Net Weight         | 1 kg      |

| Technical                                                           |                                                                                                                                        |
|---------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------|
| Rated Service Short-Circuit Breaking Capacity (I <sub>cs</sub> )    | (230 V AC) 30 kA<br>(250 V DC) 3 Poles in Series 100 kA<br>(400 V AC) 30 kA<br>(440 V AC) 18 kA<br>(500 V AC) 10 kA<br>(690 V AC) 6 kA |
| Rated Ultimate Short-Circuit Breaking Capacity (I <sub>cu</sub> )   | (230 V AC) 30 kA<br>(250 V DC) 100 kA<br>(400 V AC) 30 kA<br>(440 V AC) 18 kA<br>(500 V AC) 10 kA<br>(690 V AC) 8 kA                   |
| Rated Instantaneous Short-Circuit Current Setting (I <sub>i</sub> ) | 1120 A                                                                                                                                 |
| Setting Range                                                       | 70 ... 80 A                                                                                                                            |
| Rated Operational Power AC-3 (P <sub>e</sub> )                      | (400 V) Three Phase 45 kW                                                                                                              |
| Rated Operational Power AC-3e (P <sub>e</sub> )                     | (400 V) Three Phase 45 kW                                                                                                              |
| Rated Operational Voltage                                           | Main Circuit 690 V AC<br>Main Circuit 250 V DC                                                                                         |
| Rated Operational Current (I <sub>e</sub> )                         | 80 A                                                                                                                                   |
| Rated Operational Current AC-3 (I <sub>e</sub> )                    | 80 A                                                                                                                                   |
| Rated Operational Current AC-3e (I <sub>e</sub> )                   | 80 A                                                                                                                                   |

|                                                    |                                                                                                                                                                                                                                                                                                                                  |
|----------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Rated Operational Current DC-5 ( $I_e$ )           | 80 A                                                                                                                                                                                                                                                                                                                             |
| Rated Frequency (f)                                | Main Circuit 50 Hz<br>Main Circuit 60 Hz                                                                                                                                                                                                                                                                                         |
| Operating Frequency ( $f_{sw}$ )                   | 0 ... 415 Hz                                                                                                                                                                                                                                                                                                                     |
| Rated Impulse Withstand Voltage ( $U_{imp}$ )      | Main Circuit 8 kV                                                                                                                                                                                                                                                                                                                |
| Rated Insulation Voltage ( $U_i$ )                 | 1000 V                                                                                                                                                                                                                                                                                                                           |
| Power Loss                                         | at Rated Operating Conditions per Pole 6.27 ... 8.33 W                                                                                                                                                                                                                                                                           |
| Number of Poles                                    | 3                                                                                                                                                                                                                                                                                                                                |
| Conventional Free-air Thermal Current ( $I_{th}$ ) | Main Circuit 80 A                                                                                                                                                                                                                                                                                                                |
| Degree of Protection                               | Housing IP20<br>Main Circuit Terminals IP10                                                                                                                                                                                                                                                                                      |
| Pollution Degree                                   | 3                                                                                                                                                                                                                                                                                                                                |
| Electrical Durability                              | 20000 cycle                                                                                                                                                                                                                                                                                                                      |
| Mechanical Durability                              | 50000 cycle                                                                                                                                                                                                                                                                                                                      |
| Terminal Type                                      | Screw Terminals                                                                                                                                                                                                                                                                                                                  |
| Connecting Capacity Main Circuit                   | Flexible with Ferrule 1/2x 1 ... 35 mm <sup>2</sup><br>Flexible with Insulated Ferrule 1/2x 1 ... 35 mm <sup>2</sup><br>Flexible 1/2x 1 ... 35 mm <sup>2</sup><br>Rigid 1/2x 1 ... 4 mm <sup>2</sup><br>Solid 1/2x 1 ... 4 mm <sup>2</sup><br>Stranded 1/2x 1 ... 50 mm <sup>2</sup>                                             |
| Tightening Torque                                  | Main Circuit 4 N·m                                                                                                                                                                                                                                                                                                               |
| Wire Stripping Length                              | Main Circuit 16 mm                                                                                                                                                                                                                                                                                                               |
| Recommended Screw Driver                           | Pozidriv 2                                                                                                                                                                                                                                                                                                                       |
| Mounting Position                                  | 1 ... 6                                                                                                                                                                                                                                                                                                                          |
| Mounting on DIN Rail                               | TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715<br>TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715                                                                                                                                                                                                                   |
| Minimum Mounting Distance                          | Electrical Conductive Board, Horizontal - Up to 1000 V 1.5 mm<br>Electrical Conductive Board, Horizontal - Up to 400 V 0 mm<br>Electrical Conductive Board, Horizontal - Up to 690 V 1.5 mm<br>Electrical Conductive Board, Vertical 75 mm<br>Other Device Same Type, Horizontal 0 mm<br>Other Device Same Type, Vertical 150 mm |
| Actuator Type                                      | Rotary Handle                                                                                                                                                                                                                                                                                                                    |
| Contact Position Indication                        | ON / OFF / TRIP                                                                                                                                                                                                                                                                                                                  |
| Standards                                          | CSA 22.2 No. 14<br>IEC/EN 60947-1<br>IEC/EN 60947-2<br>IEC/EN 60947-4-1<br>UL 60947-4-1                                                                                                                                                                                                                                          |

## Technical UL/CSA

|                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|-------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Short-Circuit Current Rating (SCCR) | Manual Self-Protected Combination Controllers (Type E), (480Y / 277 V AC)<br>50 kA<br>Any UL Listed Fuses or Circuit-Breakers, Group Installations (480 V AC) 50 kA<br>Any UL Listed Fuses or Circuit-Breakers, Group Installations (600 V AC) 10 kA<br>Any UL Listed Fuses or Circuit-Breakers, Motor Disconnect (480 V AC) 50 kA<br>Any UL Listed Fuses or Circuit-Breakers, Motor Disconnect (600 V AC) 10 kA<br>Any UL Listed Fuses or Circuit-Breakers, Tap Conductor Protection in |
|-------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

|                                         |                                                                                                                                                                                                                            |
|-----------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                         | Group Installations (480Y / 277 V AC) 50 kA<br>Any UL Listed Fuses or Circuit-Breakers, Tap Conductor Protection in<br>Group Installations (600Y / 347 V AC) 10 kA                                                         |
| Maximum Operating Voltage UL/CSA        | Main Circuit 600 V AC                                                                                                                                                                                                      |
| Horsepower Rating UL/CSA                | (200 V AC) Three Phase 25 Hp<br>(208 V AC) Three Phase 25 Hp<br>(220 ... 240 V AC) Three Phase 30 Hp<br>(440 ... 480 V AC) Three Phase 60 Hp<br>(550 ... 600 V AC) Three Phase 75 Hp                                       |
| Full Load Amps Motor Use                | (110 ... 120 V AC) Three Phase 56 A<br>(200 V AC) Three Phase 78.2 A<br>(208 V AC) Three Phase 74.8 A<br>(220 ... 240 V AC) Three Phase 80 A<br>(440 ... 480 V AC) Three Phase 77 A<br>(550 ... 600 V AC) Three Phase 77 A |
| Locked Rotor Amps                       | (200 V AC) Three Phase 420 A<br>(208 V AC) Three Phase 404 A<br>(220 ... 240 V AC) Three Phase 435 A<br>(440 ... 480 V AC) Three Phase 435 A<br>(550 ... 600 V AC) Three Phase 434 A                                       |
| General Use Rating UL/CSA               | (600 V AC) 80 A                                                                                                                                                                                                            |
| Connecting Capacity Main Circuit UL/CSA | Flexible 1/2x 16-0 AWG<br>Stranded 1/2x 16-0 AWG                                                                                                                                                                           |
| Tightening Torque UL/CSA                | Main Circuit 35 in-lb                                                                                                                                                                                                      |

Environmental

|                                            |                                                                                            |
|--------------------------------------------|--------------------------------------------------------------------------------------------|
| Ambient Air Temperature                    | Operation -25 ... +60 °C<br>Operation Compensated -25 ... +60 °C<br>Storage -50 ... +80 °C |
| Ambient Air Temperature Compensation       | Yes                                                                                        |
| Maximum Operating Altitude Permissible     | 2000 m                                                                                     |
| Resistance to Shock acc. to IEC 60068-2-27 | 11 ms Pulse 25g                                                                            |
| Resistance to Vibrations                   | Mounted on Mounting Plate: 5g 3 ... 150 Hz<br>Mounted on DIN-Rail: 4g 3 ... 150 Hz         |

Material Compliance

|                                             |                                                                        |
|---------------------------------------------|------------------------------------------------------------------------|
| Conflict Minerals Reporting Template (CMRT) | 9AKK108467A5658                                                        |
| REACH Declaration                           | 1SAA963005-4502                                                        |
| RoHS Information                            | 1SAA963006-4502                                                        |
| RoHS Status                                 | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
| Toxic Substances Control Act - TSCA         | 2CMT2023-006539                                                        |
| WEEE B2C / B2B                              | Business To Business                                                   |
| WEEE Category                               | 5. Small Equipment (No External Dimension More Than 50 cm)             |

Circular Value

|                          |                |
|--------------------------|----------------|
| End of Life Instructions | 1SAC00284H0001 |
|--------------------------|----------------|

## Certificates and Declarations

|                                  |                                      |
|----------------------------------|--------------------------------------|
| ATEX Certificate                 | 1SAA918001-3901                      |
| CB Certificate                   | 1SAA918002-2002                      |
| CQC Certificate                  | CQC2015010307760141                  |
| Cut-off Current Characteristic   | 1SAM400507F0001                      |
| Declaration of Conformity - CCC  | 2020980307003042                     |
| Declaration of Conformity - CE   | 1SAD101100-3408                      |
| Declaration of Conformity - UKCA | 1SAD201100-3408                      |
| EAC Certificate                  | 1SAA963000-2701                      |
| I <sup>2</sup> t Characteristic  | 1SAM400506F0001                      |
| IECEx Certificate                | 1SAA918000-4001                      |
| UL Certificate                   | E137861-20150206<br>E345003-20150206 |

## Container Information

|                                |                 |
|--------------------------------|-----------------|
| Package Level 1 Units          | box 1 piece     |
| Package Level 1 Width          | 64 mm           |
| Package Level 1 Depth / Length | 177 mm          |
| Package Level 1 Height         | 140 mm          |
| Package Level 1 Gross Weight   | 1.1 kg          |
| Package Level 1 EAN            | 4013614536632   |
| Package Level 2 Units          | carton 12 piece |
| Package Level 2 Width          | 330 mm          |
| Package Level 2 Depth / Length | 400 mm          |
| Package Level 2 Height         | 320 mm          |
| Package Level 2 Gross Weight   | 13 kg           |
| Package Level 2 EAN            | 4013614537820   |

## Classifications

|                                    |                                             |
|------------------------------------|---------------------------------------------|
| Object Classification Code         | F                                           |
| ETIM 5                             | EC000074 - Motor protective circuit-breaker |
| ETIM 6                             | EC000074 - Motor protection circuit-breaker |
| ETIM 7                             | EC000074 - Motor protection circuit-breaker |
| ETIM 8                             | EC000074 - Motor protection circuit-breaker |
| eClass                             | V11.0 : 27370401                            |
| UNSPSC                             | 39121521                                    |
| IDEA Granular Category Code (IGCC) | 4731 >> Manual Starters                     |
| E-Number (Finland)                 | 3708084                                     |
| E-Number (Sweden)                  | 3110789                                     |

## Accessories

| Identifier      | Description                                                            | Type      | Quantity | Unit Of Measure |
|-----------------|------------------------------------------------------------------------|-----------|----------|-----------------|
| 1SAM201901R1001 | HKF1-11 Aux.-contact for front mounting                                | HKF1-11   | 1        | piece           |
| 1SAM201901R1201 | HKF1-11K Aux.-contact for frontmounting with Push-In terminals         | HKF1-11K  | 1        | piece           |
| 1SAM201901R1002 | HKF1-20 Aux.-contact 2NO, front mounting                               | HKF1-20   | 1        | piece           |
| 1SAM201901R1202 | HKF1-20K Aux.-contact for frontmounting with Push-In terminals         | HKF1-20K  | 1        | piece           |
| 1SAM201901R1004 | HKF1-01 Aux.-contact for front mounting                                | HKF1-01   | 1        | piece           |
| 1SAM201901R1003 | HKF1-10 Aux.-contact for front mounting                                | HKF1-10   | 1        | piece           |
| 1SAM201902R1002 | HK1-20 Aux.-contact 2 NO                                               | HK1-20    | 1        | piece           |
| 1SAM201902R1202 | HK1-20K Aux.-contact 2 NO with Push-In terminals                       | HK1-20K   | 1        | piece           |
| 1SAM201902R1001 | HK1-11 Aux.-contact 1 NO + 1 NC                                        | HK1-11    | 1        | piece           |
| 1SAM201902R1201 | HK1-11K Aux.-contact 1 NO + 1 NC with Push-In terminals                | HK1-11K   | 1        | piece           |
| 1SAM201902R1003 | HK1-02 Aux.-contact 2 NC                                               | HK1-02    | 1        | piece           |
| 1SAM201902R1203 | HK1-02K Aux.-contact 2 NC with Push-In terminals                       | HK1-02K   | 1        | piece           |
| 1SAM201902R1004 | HK1-20L Aux.-cont. w. 2 lead contacts 2 NO                             | HK1-20L   | 1        | piece           |
| 1SAM201902R1204 | HK1-20LK Aux.-cont. w. 2 leading contacts 2 NO, with Push-In terminals | HK1-20LK  | 1        | piece           |
| 1SAM201903R1002 | SK1-20 Signaling Contact 2 NO                                          | SK1-20    | 1        | piece           |
| 1SAM201903R1202 | SK1-20K Signaling Contact 2 NO with Push-In terminals                  | SK1-20K   | 1        | piece           |
| 1SAM201903R1005 | SK1-20AR Signaling Contact, 2NO with screw terminals                   | SK1-20AR  | 1        | piece           |
| 1SAM201903R1205 | SK1-20ARK Signaling Contact, 2NO with Push-in Spring terminals         | SK1-20ARK | 1        | piece           |
| 1SAM201903R1001 | SK1-11 Signaling Contact 1 NO + 1 NC                                   | SK1-11    | 1        | piece           |
| 1SAM201903R1201 | SK1-11K Signaling Contact 1 NO + 1 NC with Push-In terminals           | SK1-11K   | 1        | piece           |
| 1SAM201903R1004 | SK1-11AR Signaling Contact, 1NO+1NC with screw terminals               | SK1-11AR  | 1        | piece           |
| 1SAM201903R1204 | SK1-11ARK Signaling Contact, 1NO+1NC with Push-in Spring terminals     | SK1-11ARK | 1        | piece           |
| 1SAM201903R1003 | SK1-02 Signaling Contact 2 NC                                          | SK1-02    | 1        | piece           |
| 1SAM201903R1203 | SK1-02K Signaling Contact 2 NC with Push-In terminals                  | SK1-02K   | 1        | piece           |
| 1SAM201903R1006 | SK1-02AR Signaling Contact, 2NC with screw terminals                   | SK1-02AR  | 1        | piece           |
| 1SAM201903R1206 | SK1-02ARK Signaling Contact, 2NC with Push-in Spring terminals         | SK1-02ARK | 1        | piece           |
| 1SAM301901R1002 | CK1-20 Short-Circuit Signaling Contact 2 NO                            | CK1-20    | 1        | piece           |
| 1SAM301901R1001 | CK1-11 Short-Circuit Signaling Contact 1 NO + 1 NC                     | CK1-11    | 1        | piece           |
| 1SAM301901R1003 | CK1-02 Short-Circuit Signaling Contact 2 NC                            | CK1-02    | 1        | piece           |
| 1SAM201910R1001 | AA1-24 Shunt Trip 20-24V                                               | AA1-24    | 1        | piece           |
| 1SAM201910R1002 | AA1-110 Shunt Trip 110V                                                | AA1-110   | 1        | piece           |
| 1SAM201910R1003 | AA1-230 Shunt Trip 200-240V                                            | AA1-230   | 1        | piece           |
| 1SAM201910R1004 | AA1-400 Shunt Trip 350-415V                                            | AA1-400   | 1        | piece           |
| 1SAM201904R1010 | UA1-20 Undervoltage release 20V 50Hz / 24V 60 Hz                       | UA1-20    | 1        | piece           |
| 1SAM201904R1001 | UA1-24 Undervoltage release 24 V                                       | UA1-24    | 1        | piece           |
| 1SAM201904R1002 | UA1-48 Undervoltage release 48V                                        | UA1-48    | 1        | piece           |
| 1SAM201904R1003 | UA1-60 Undervoltage release 60V                                        | UA1-60    | 1        | piece           |

|                 |                                                                              |             |   |       |
|-----------------|------------------------------------------------------------------------------|-------------|---|-------|
| 1SAM201904R1004 | UA1-110 Undervoltage release 110V 110V<br>50Hz/120V 60Hz                     | UA1-110     | 1 | piece |
| 1SAM201904R1008 | UA1-208 Undervoltage release 208V 60Hz                                       | UA1-208     | 1 | piece |
| 1SAM201904R1005 | UA1-230 Undervoltage release 230 V 50 Hz /<br>240 V 60 Hz                    | UA1-230     | 1 | piece |
| 1SAM201904R1006 | UA1-400 Undervoltage release 400V                                            | UA1-400     | 1 | piece |
| 1SAM201904R1007 | UA1-415 Undervoltage release 415V 415V<br>50Hz/480V 60Hz                     | UA1-415     | 1 | piece |
| 1SAM201904R1009 | UA1-575 Undervoltage release 575V 60Hz                                       | UA1-575     | 1 | piece |
| 1SAM401923R1003 | S2-M3-50 3-phase Power infeed Block for<br>MS165, 50 mm <sup>2</sup>         | S2-M3-50    | 1 | piece |
| 1SAM401920R1002 | PS2-2-0-125 3-phase busbar for 2 MS165,<br>Ie=125A                           | PS2-2-0-125 | 1 | piece |
| 1SAM401920R1003 | PS2-3-0-125 3-phase busbar for 3 MS165,<br>Ie=125A                           | PS2-3-0-125 | 1 | piece |
| 1SAM401920R1004 | PS2-4-0-125 3-phase busbar for 4 MS165,<br>Ie=125A                           | PS2-4-0-125 | 1 | piece |
| 1SAM401920R1022 | PS2-2-2-125 3-phase busbar for 2 MS165 with 2<br>HK/SK, Ie=125A              | PS2-2-2-125 | 1 | piece |
| 1SAM401920R1023 | PS2-3-2-125 3-phase busbar for 3 MS165 with 2<br>HK/SK, Ie=125A              | PS2-3-2-125 | 1 | piece |
| 1SAM401920R1024 | PS2-4-2-125 3-phase busbar for 4 MS165 with 2<br>HK/SK, Ie=125A              | PS2-4-2-125 | 1 | piece |
| 1SAM401921R1001 | BS2-3 Protection Cover for busbars                                           | BS2-3       | 1 | piece |
| 1SAM401922R1001 | KA165 Terminal Shroud for MS165/MO165                                        | KA165       | 1 | piece |
| GJF1101903R0002 | SA2 Terminals and Installation Material                                      | SA2         | 1 | piece |
| 1SAM201920R1011 | MSHD-LTB Handle, IP64, black, 3 times<br>lockable, defeatable, 0-TRIP-I      | MSHD-LTB    | 1 | piece |
| 1SAM201920R1012 | MSHD-LTY Handle, IP64, red/yellow, 3 times<br>lockable, defeatable, 0-TRIP-I | MSHD-LTY    | 1 | piece |
| 1SAM201920R1000 | MSH-AR Shaft alignment ring suitable for<br>MSHD and MSH handles             | MSH-AR      | 1 | piece |
| 1SAM101923R0002 | MSMN Driver w. screw for manual motor<br>stators, 6x6                        | MSMN        | 1 | piece |
| 1SAM101923R0012 | MSMNO Driver w/o coding w. screw for manual<br>motor stators, 6x6            | MSMNO       | 1 | piece |
| 1SCA101647R1001 | OXS6X85 SHAFT                                                                | OXS6X85     | 1 | piece |
| 1SCA108043R1001 | OXS6X105 SHAFT                                                               | OXS6X105    | 1 | piece |
| 1SCA101655R1001 | OXS6X130 SHAFT                                                               | OXS6X130    | 1 | piece |
| 1SCA101659R1001 | OXS6X180 SHAFT                                                               | OXS6X180    | 1 | piece |

## Categories

Low Voltage Products and Systems → Circuit Breakers → Manual Motor Starters

Low Voltage Products and Systems → Control Products → Manual Motor Starters → Manual Motor Starters

