

PRODUCT-DETAILS

# ACS580-01-05A7-4+0J400

LV AC general purpose wall-mounted drive, IEC: Pn 2.2 kW, 5.6 A (ACS580-01-05A7-4+0J400)



General Information	
Global Commercial Alias	ACS580-01-05A7-4+0J400
Product ID	3ABD00046125
ABB Type Designation	ACS580-01-05A7-4+0J400
Catalog Description	LV AC general purpose wall-mounted drive, IEC: Pn 2.2 kW, 5.6 A (ACS580-01-05A7- 4+0J400)
Long Description	The ACS580-01 is plug-in ready to control your compressors, conveyors, pumps, extruders, centrifuges, mixers, fans, and many other variable and constant torque applications, in a variety of light industries, including food and beverage, plastic, textile, material handling, and agriculture. All essential features are built-in as standard, simplifying drive selection, and making additional hardware unnecessary. A versatile and straightforward settings menu and assistants enable fast setup, commissioning, use, and maintenance, while a rugged and robust design make it a good fit for various environments. With the ACS580 drives, you can easily take full control of your processes to comprehensively manage your plant. The wall-mounted ACS580-01 comes in an IP21 enclosure as standard. In addition, IP55 and flange mounting units are available.

Ord	lerin	g

Country of Origin China (CN)

Customs Tariff Number	85044099
Invoice Description	ACS580-01-05A7-4+0J400 PN: 2.2kW, IN:5.6A
Made To Order	No
Minimum Order Quantity	1 piece
Order Multiple	1 piece
Quote Only	No
Selling Unit of Measure	piece

Dimensions		
Product Net Weight	6.5 kg	
Product Net Depth / Length	223 mm	
Product Net Height	303 mm	
Product Net Width	125 mm	
Package Level 1 Units	0 carton	

Technical	
Number of Phases	3
Degree of Protection	IP21
Enclosure Type NEMA	Type1
Frequency (f)	47.5 63 Hz
Frame Size	R1
Input Voltage (U <sub>in</sub> )	380 480 V
Mounting Type	Wall-mounted_NO UNIT\$
Output Current, Heavy-	4 A
Duty Use (I <sub>HD</sub> )	
Output Current, Light-	5.3 A
Overload Use ( $I_{LD}$ )	
Output Current, Normal	5.6 A
Use (l <sub>n</sub> )	
Output Power, Heavy-	1.5 kW
Duty Use (P <sub>HD</sub> )	
Output Power, Light-	2.2 kW
Overload Use ( $P_{LD}$ )	
Output Power, Normal	2.2 kW
Use (P <sub>n</sub> )	
Efficiency Level	IE2
Consulate Differ Module	

Complete Drive Module Efficiency (61800-9-2) ACS580-01-05A7-4+0J400 3/3

Operating Point Frequency / Current	Absolute Loss	Relative Loss	Efficiency
0 / 25 %	41 W	1.1 %	83.3 %
0 / 50 %	47 W	1.2 %	89.4 %
0 / 100 %	62 W	1.6 %	92.3 %
50 / 25 %	43 W	1.1 %	90.8 %
50 / 50 %	51 W	1.3 %	94.2 %
50 / 100 %	70 W	1.8 %	95.6 %
90 / 50 %	56 W	1.5 %	96.3 %
90 / 100 %	85 W	2.2 %	97.0 %

### Classifications

UNSPSC 39122001

#### **Environmental**

WEEE Category 5. Small Equipment (No External Dimension More Than 50 cm)

#### **Additional Information**

Product Name Frequency Converter

## **Categories**

